



Commercial and Industrial Air-conditioners

Capacity from 9,350 to 203,000 BTU/Hr.

Model	CCU-H 09	10	12	16	18	20	25	28	33	35	38	44	48	56	60	63
Cooling Capacity	9,350	10,000	12,500	16,100	18,300	20,000	25,800	28,300	33,400	36,000	38,700	44,100	48,000	56,200	60,830	63,430
V.-Ph.-Hz.	220-1-50															
Compressor	4.16	4.4	5.3	7.4	7.8	8.6	10.9	12.1	14.7/5.3	15.2/5.5	16.4/6.1	17.6/8.6	9.1	8.6	9.1	9.2
h.p.	1	1	1.6	1.7	2	2.5	2.83	3.3	3.3	3.5	3.75	4.5	4.75	5.75	6	6
Watt	80															
V.-Ph.-Hz.	220-1-50															
amps.	0.37															
rpm.	900															
cfm.	1,500															
inch.	1.800															
inch.	16															
type	R-22															
sq.ft.	4,444															
row	1															
fin/inch.	1/2															
inch.	1/4															
inch.	52x75x47															
cm.	52x75x52															
kg.	52															
kg.	53															
kg.	57															
kg.	67															
kg.	68															
kg.	68															
kg.	68															
kg.	75															
kg.	75															
kg.	76															
kg.	76															
kg.	79															
kg.	84															
kg.	84															
kg.	86															
kg.	86															
kg.	99															
kg.	99															
kg.	100															
kg.	100															
kg.	101.11															
kg.	1.33															
kg.	1.75															
kg.	1.9															
kg.	1.9															
kg.	2															
kg.	2															
kg.	14															
kg.	5/8															
kg.	3/8															
kg.	3/8															
kg.	58x85x67															
kg.	58x85x62															
kg.	58x85x62															
kg.	63x95x72															
kg.	63x95x72															
kg.	63x95x78															
kg.	63x95x78															
kg.	110															
kg.	110															

Model : CCU-H 09-63



Model	CCU-H 77	85	105	122	154	203
Cooling Capacity	77,100	85,000	105,000	122,000	154,000	203,000
V.-Ph.-Hz.	380-3-50					
Compressor type	Hermetic					
Compressor type	Semi-Hermetic / Hermetic					
h.p.	8	9	10	12	15	20
V.-Ph.-Hz.	380-3-50					
amps.	12.4	13.7	15.9	17.9	27.6	32.3
Watt	420	420	760	1,340		
V.-Ph.-Hz.	380-3-50					
amps.	0.90	0.90	1.6		4.15	
rpm.	900					
cfm.	4,500					
inch.	10,000					
inch.	24					
type	R-22					
sq.ft.	12.44					
row	3					
fin/inch.	14					
inch.	1-1/8					
inch.	5/8					
cm.	83x108x78					
kg.	130					
kg.	350					
kg.	360					
kg.	400					
kg.	400					
kg.	450					
kg.	450					

Model : CCU-H 77-203



ISO 9001 : 2000

NOTE @ COOLING CAPACITY BASED ON ENTERING AIR TEMP. 80 F. DB/67 F.WB.AMBIENT TEMP. 95 F.DB. SPECIFICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE. (หมายเหตุ ความสามารถทำความเย็นขึ้นอยู่กับอุณหภูมิอากาศเข้า)