

# Central Air Floor Standing Type



Model : CFP-N



Model : CFP-LX

## เซ็นทรัลแอร์ ประหยัดไฟ...ใช้นานปี

- Quiet Operation
- Slim & Luxurious Design
- Digital Touch Screen Display
- Automatic Directional Air Flow
- Fully Function of Floor Standing Type



ISO 9001 : 2000



# Floor Standing Type

เครื่องปรับอากาศ เซ็นทรัลแอร์ แบบตู้ตั้ง

Model : CFP



## SPECIFICATIONS-Floor Standing Type Split Unit

Model : CFP		33-38	44-48	56-63	77-85	105-122	154	
Cooling Capacity	BTU./Hr.	33,400-38,700	44,100-48,000	56,200-63,400	77,100-85,000	105,000-122,000	154,000	
Air Flow	CFM.	1200	1600	2000	3000	4000	5500	
Evaporator	Coil	Type	Plate Fin					
		Rows	3			4		
		Face Area (Sq.Ft.)	2.67	3.33	4	5.75	7.81	11.56
		Tube Size (In.)	3/8					
	Blower	Size (In.)	8 x 7	8 x 9	8 x 10	9 x 9	10 x 10	10 x 10
		Type	Centrifugal Direct Drive					
		Qt.	2					3
	Motor	H.P.	1/6	1/4	1/4	1/3 x 2	1/2 x 2	1/2 x 3
		R.P.M.	900 / 850 / 750					
		V/Ph./Hz.	220 / 1 / 50					
F.L.A. (Amp.)		1.3	1.8	1.8	2.3 x 2	3.5 x 2	3.5 x 3	
Thermostat		Built-In						
Drain Pipe Dia.	Inch	3/4						
Weight (Kg.)	(APPROX.)	110	115	122	148	190	270	
Dimensions (mm.)	Length	857	959	1,162	1,162	1,467	1,702	
	Height	1,753			1,905			1,994
	Depth	419			508			



ISO 9001 : 2000

## SPECIFICATIONS-Floor Standing Type Split Unit

Model	Indoor	CFP-LX 18-25	CFP-N 33-38	CFP-N 44-48	CFP-N 56	CFP-N 60-63		
Nominal Cooling Capacity	Btu./Hr.	18,000-25,000	33,400-38,700	44,100-48,000	56,200	60,833-63,000		
	Kw.	2.63	5.28	7.03	8.79	10.55		
Nominal air circulation	CFM	1,000	1,000	1,700	1,700	1,700		
Fan Indoor	Type	Permanent split capacitor						
	Nominal power output	W	80	50	250	250	250	
	FLA.	A	0.6	0.64	2.50	2.50	2.50	
	Speed	RPM	560	680	650	650	650	
	Power Source	V/Ph./Hz.	220 / 1 / 50					
	Quantity		1	1	1	1	1	
	Noise Level (Low/High)	dBA	42/45	42/45	44/47	44/47	44/47	
Drive Method	Direct/Belt	Direct						
Coil	Type	Coated Aluminium Fin and Inner grooved						
	Face Area	ft <sup>2</sup>	2.65	2.5	4.8	4.8	4.8	
	Rows / FPI		2/18	3/14	4/14	4/14	4/14	
Operation Control Type		Wireless Controller						
Weight	Unit	Kg.	37	43	65	65	65	
	Packing	Kg.	46	46	69	69	69	
Unit Dimension	Depth	mm.	323	250	345	345	345	
	Length	mm.	539	480	605	605	605	
	Height	mm.	1,744	1,680	1,900	1,900	1,900	
Drain Pipe Dia.	inch	3/4	3/4	3/4	3/4	3/4		
Power supply	V/Ph./Hz.	220 / 1 / 50						

Specifications are subjected to changes without notice for product development. Notes : 1. Nominal cooling capacities are base on the following conditions.

Indoor : 27°CDB, 19.0°CWB, Outdoor : 35°CDB, 24°CWB 2. Nominal heating capacities are base on the following conditions. Indoor : 20°CDB, Outdoor : 7°CDB, 6°CWB